


## ARDEX K 220

### Professional Commercial Floor Levelling and Smoothing Compound

ARDEX K 220 is a levelling and smoothing compound designed to level and smooth internal sub-floors prior to applying floor finishes. **LOW VOC** 

#### LOCATION

- Internal sub-floors

#### SUBSTRATES

- Internal, dry concrete substrates

#### FLOOR COVERINGS

- Linoleum, vinyl, carpet
- Ceramic and quarry tiles
- Floating Timber

#### COVERAGE

- 4m<sup>2</sup> at 3mm thick

#### THICKNESS

- From 2 - 20mm in one application without aggregate
- For thickness over 20mm, K 220 can be applied to 30mm in one application when used with aggregate

#### DRYING TIME

- Allow approximately 2-3 hours at 23°C and 50% relative humidity, before foot traffic
- Conventionally laid carpet and floating floors can be installed after 24 hours
- Direct stick applications such as vinyl flooring after 48 hours. Allow longer for humid climates and low temperatures

#### PACKAGING

- 20kg bag

#### CODE

23240



#### ARDEX K 220 QUICK FACTS

- Quick Drying – walkable after only 2-3 hours
- Easy to install – 2mm to 20mm in one application
- Suitable for residential and commercial applications
- Very low odour – ideal for enclosed environments



#### CONTACT US

1300 788 780 | [www.ardexaustralia.com](http://www.ardexaustralia.com)



Download the Ardex app  
(search for 'ARDEX Australia')



**SYSTEMARDEX**  
PREMIUM PERFORMANCE