# **ARDEX WPM 155 FAST-DRYING UNDERTILE POLYURETHANE MEMBRANE**

ARDEX WPM 155 Rapid is a water-based, modified polyurethaneacrylic liquid membrane developed for high performance under-tile waterproofing. ARDEX WPM 155 Rapid's fast-drying formula allows areas to be tiled in 4 hours and provides extended coverage for minimal cost.

### Benefits

- · Tough, flexible film
- Tile in 4 hours
- Long shelf life ٠
- Excellent adhesion with ARDEX Tile Adhesives
- Environmentally friendly solvent free
- Meets Green Building Council of Australia Greenstar requirements IEQ-13 & IEQ-11
- Class III Membrane as per AS/NZS4858 Wet Area Membranes
- Use with ARDEX STB and STA tapes

#### Location

- Commercial or Residential
- Internal or External
- Wet areas, balconies, decks, bathrooms
- Under tiling

#### Coverage

- Floors: 0.6m<sup>2</sup>/litre
- Walls: 1.1m<sup>2</sup>/litre

## **Drying Times**

- Recoat time: 1-2 hours
- Ready to tile: 4-6 hours
- · Full cure: 3 days
- Render and Screeds
- Fibre-Cement Sheets (wet area grade) •
- Plywood
- Plasterboard

Packaging	Code
4L	41064
15L	19727







Download the ARDEX app App Store

search for: 'ARDEX New Zealand'

Substrates • Concrete



