


ARDEX AF 271

Pressure Sensitive Carpet Tile Adhesive

ARDEX AF 271 acrylic water based carpet tile adhesive for internal use free of hazardous organic solvents. **LOW VOC** 

- Pressure sensitive adhesive for semi permanent (releasable) carpet tile and underlay installation
- Can be installed using a long nap roller or 1.6mm “V” notched trowel
- Excellent initial grab for permanent underlay and carpet tile installation

LOCATION

- Internal

SUBSTRATES

ARDEX AF 271 is designed to bond carpet tile and carpet pad underlay onto:

- Concrete
- Timber
- Terrazzo.

FLOOR COVERINGS

- Vinyl backed carpet tile
- Non-vinyl backed carpet tile for permanent application

COVERAGE

- Using short to medium nap roller approximately 8–10m²/L
- Using a 1.6x1.6x1.6mm V-Notch trowel approximately 5.0m²/L for the installation of VCT & textured backed carpet tiles and double bond underlays

WORKING TIME

- Increased working time for semi-permanent carpet tile installation providing that the adhesive is not exposed to dust and other contaminants

SET UP TIME

- 15–30 minutes for semi-permanent carpet tile installation depending on site ambient conditions

PACKAGING

- 15L pail containing 18kg of adhesive

CODE

38565



ARDEX AF 271 QUICK FACTS

- For the installation of vinyl and non vinyl backed carpet tiles
- Direct stick and double bond installation



SYSTEMARDEX
PREMIUM PERFORMANCE

CONTACT US
0800 227 339 | ardex.co.nz