

## Ardex WPM 002 Superflex Two Part Liquid

Ardex (Ardex NZ)

Chemwatch: 5022-79 Version No: 5.1.1.1

Safety Data Sheet according to HSNO Regulations

Issue Date: 29/12/2015 Print Date: 15/02/2016 Initial Date: Not Available S.GHS.NZL.EN

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### **Product Identifier**

Product name	Ardex WPM 002 Superflex Two Part Liquid
Synonyms	ABA superflex Liquid waterproofing membrane, fromer name: Superflex Bathroom & Balcony Two Part Liquid
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

The liquid component of two part Superflex waterproof coating. When mixed with the powder component in accordance with manufacturers directions, can be Relevant identified uses applied over conventional surfaces in wet areas and balconies. Will dry to form a flexible and tough waterproof membrane. Applied by brush or roller.

### Details of the supplier of the safety data sheet

Registered company name	Ardex (Ardex NZ)	Ardex (Ardex Australia)	
Address 32 Lane Street Woolston Christchurch New Zealand		20 Powers Road Seven Hills 2147 NSW Australia	
Telephone	+64 3373 6928	1800 224 070	
Fax	+64 3384 9779	1300 780 102	
Website	Not Available	Not Available	
Email	Not Available	Not Available	

### **Emergency telephone number**

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	+64 3373 6900	1800 224 070 (Mon-Fri, 9am-5pm)
Other emergency telephone numbers	Not Available	Not Available

### **SECTION 2 HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

### CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	0		0 = Minimum
Body Contact	1		1 = Low 2 = Moderate
Reactivity	0		3 = High
Chronic	Λ		4 = Extreme

Classification	Not Applicable
Determined by Chemwatch using GHS/HSNO criteria	Not Available

Label elements	
GHS label elements	Not Applicable
SIGNAL WORD	NOT APPLICABLE

### Ardex WPM 002 Superflex Two Part Liquid

Issue Date: **29/12/2015**Print Date: **15/02/2016** 

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

### Substances

See section below for composition of Mixtures

### Mixtures

mixta o		
CAS No	%[weight]	Name
		polymer dispersion as
Not Available	<60	acrylic resin.
Not Available	<1	residual acrylic monomer
Not Available	<1	biocide
Not Available	<5	natural fibre
Not Available	<5	additives, unspecified
7732-18-5	balance	<u>water</u>
		No other ingredient information disclosed.

### **SECTION 4 FIRST AID MEASURES**

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

### Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ▶ Flush skin and hair with running water (and soap if available).  ▶ Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5 FIREFIGHTING MEASURES**

### Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.	
Advice for firefighters		
Fire Fighting	<ul> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>Do not approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> </ul>	
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> </ul>	

### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

Minor Spills

► Clean up all spills immediately.

Chemwatch: **5022-79** Page **3** of **7** 

Version No: **5.1.1.1** 

### Ardex WPM 002 Superflex Two Part Liquid

Issue Date: **29/12/2015**Print Date: **15/02/2016** 

	<ul> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Prevent spillage from entering drains, sewers or water courses.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 HANDLING AND STORAGE**

### Precautions for safe handling

Safe handling	<ul> <li>Limit all unnecessary personal contact.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Avoid contact with incompatible materials.</li> </ul>
Other information	Keep dry.     Store under cover.     Protect containers against physical damage.     Observe manufacturer's storage and handling recommendations contained within this SDS.

### Conditions for safe storage, including any incompatibilities

Suitable container	Multi-ply paper bag with sealed plastic liner or heavy gauge plastic bag.  NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Check that all containers are clearly labelled and free from leaks. Packing as recommended by manufacturer.
Storage incompatibility  Avoid contamination of water, foodstuffs, feed or seed.  None known	

### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

### **Control parameters**

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Ardex WPM 002 Superflex Two Part Liquid	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
acrylic resin.	Not Available		Not Available	
residual acrylic monomer	Not Available		Not Available	
biocide	Not Available		Not Available	
natural fibre	Not Available		Not Available	
additives, unspecified	Not Available		Not Available	
water	Not Available		Not Available	

### **Exposure controls**

# Appropriate engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

# Eye and face protection

- ► Safety glasses with side shields
- Chemical goggles.
  - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

### Skin protection See Hand protection below

### Wear general protective gloves, eg. light weight rubber gloves.

### Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Ardex WPM 002 Superflex Two Part Liquid

Issue Date: 29/12/2015 Print Date: 15/02/2016

	The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities.  OTHERWISE:  Overalls.  Barrier cream.  Eyewash unit.
Thermal hazards	Not Available

### Recommended material(s)

### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the  $\ensuremath{\textit{computer-generated}}$  selection:

Ardex WPM 002 Superflex Two Part Liquid

Material	СРІ
BUTYL	А
NEOPRENE	А
VITON	А
NATURAL RUBBER	С
PVA	С

<sup>\*</sup> CPI - Chemwatch Performance Index

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

Not Available

Not Applicable

### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Milky white emulsion with a characteristic odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1.04
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.5-9.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100 approx	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	45-47
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

## Page 5 of 7 Ardex WPM 002 Superflex Two Part Liquid

Issue Date: 29/12/2015 Print Date: 15/02/2016

Hazardous decomposition products

See section 5

### **SECTION 11 TOXICOLOGICAL INFORMATION**

### Information on toxicological effects

Inhaled	The vapour may produce discomfort of the upper respiratory tract. Inhalation hazard is increased at higher temperatures.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
Eye	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Chronic	Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following.  As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.  Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures.

Ardex WPM 002 Superflex Two Part Liquid	TOXICITY  Not Available	IRRITATION  Not Available
water	TOXICITY  Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	IRRITATION  Not Available
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Ardex WPM 002 Superflex Two Part Liquid	Concentration of monomers is normally so low that they are not considered a significant hazard under conditions of good occupational work practice.		
WATER	No significant acute toxicological data identified in literature search.		
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

— Data available but does not fill the criteria for classification
 — Data required to make classification available

### **SECTION 12 ECOLOGICAL INFORMATION**

### Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
water	EC50	384	Crustacea	199.179mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	LC50	96	Fish	897.520mg/L	3
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconceptration Data 7. METI (Japan) - Bioconceptration Data 8. Vendor Data				

### DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

# Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

### Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

### Ardex WPM 002 Superflex Two Part Liquid

Issue Date: 29/12/2015 Print Date: 15/02/2016

### **SECTION 13 DISPOSAL CONSIDERATIONS**

### Waste treatment methods

### ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.

- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- · Where in doubt contact the responsible authority.
- Product / Packaging

  disposal

  Recycle wherever possible

  Consult manufacturer for re
  - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility
    can be identified.
  - Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
  - Decontaminate empty containers.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

### **SECTION 14 TRANSPORT INFORMATION**

### Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### **SECTION 15 REGULATORY INFORMATION**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
Not Applicable	Not Applicable

### WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

### **Location Test Certificate**

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

### **Approved Handler**

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

### **Tracking Requirements**

Not Applicable

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (water)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water)
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory  N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

Chemwatch: 5022-79 Page 7 of 7 Issue Date: 29/12/2015 Version No: 5.1.1.1

### Ardex WPM 002 Superflex Two Part Liquid

Print Date: 15/02/2016

### **SECTION 16 OTHER INFORMATION**

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.