

ARDEX AF 178

Universal Sheet Vinyl Adhesive

ARDEX AF 178 is an internal water based acrylic co-polymer blend adhesive designed for experienced applicators who install sheet vinyl floor coverings in commercial and retail premises. ARDEX AF 178 has excellent workability, longer working time and effective plasticiser migration resistance. **LOW VOC** ★

LOCATION

- Permanent internal application

SUBSTRATES

- Hardboard underlayment board approved to AS 2458, cementitious underlayment and dry concrete with moisture content that complies with AS 1884:2012. Contact ARDEX Technical Services for other substrates including terrazzo, ceramic tiles and metal substrates.

FLOOR COVERINGS

- Sheet vinyl and vinyl planks coverings in permanent applications

COVERAGE

- Using 1.6mm V1 notch trowel approximately 5m²/L

WORKING TIME

- 60 minutes

SET UP TIME

- Approximately 15 - 25 minutes

PACKAGING

- 15L pail containing 18kg of adhesive

CODE

12971



ARDEX AF 178 QUICK FACTS

- Water based acrylic co-polymer bond
- Long working time of 60 minutes
- Outstanding initial grab
- Fast setup start installation faster



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE