FLOORING

ARDEX AF 271

Pressure Sensitive Carpet Tile Adhesive

ARDEX AF 271 acrylic water based carpet tile adhesive for internal use free of hazardous organic solvents. Low voc

- Pressure sensitive adhesive for semi permanent (releasable) carpet tile and underlay installation
- · Can be installed using a long nap roller or 1.6mm "V" notched trowel
- Excellent initial grab for permanent underlay and carpet tile installation

LOCATION

Internal

SUBSTRATES

ARDEX AF 271 is designed to bond carpet tile and carpet pad underlay onto:Hardboard underlay approved to AS 1859

- Concrete
- Timber
- Terrazzo.

FLOOR COVERINGS

- · Vinyl backed carpet tile
- · Non-vinyl backed carpet tile for permanent application

COVERAGE

- Using short to medium nap roller approximately 8–10m²/L
- Using a 1.6x1.6x1.6mm V-Notch trowel approximately 5.0m²/L for the installation of VCT & textured backed carpet tiles and double bond underlays

WORKING TIME

 Increased working time for semi-permanent carpet tile installation providing that the adhesive is not exposed to dust and other contaminants

SET UP TIME

 15–30 minutes for semi-permanent carpet tile installation depending on site ambient conditions

PACKAGING

15L pail containing 18kg of adhesive

CODE 38565





App Store

1300 788 780 www.ardexaustralia.com

Google play

Download the Ardex app (search for 'ARDEX Australia')



ARDEX AF 271 QUICK FACTS

- For the installation of vinyl and non vinyl backed carpet tiles
- Direct stick and double bond installation

