

# SELF-LEVELLING AND SMOOTHING COMPOUND

## ARDEX ARDITEX NA

### Universal Self-Levelling and Smoothing Compound

ARDITEX NA is formulated with excellent adhesion designed to work perfectly under a damp proof membrane. Also used to pre-level existing timber floors prior to the installation of timber sheeting for a stable base for new floor coverings.

LOW VOC 

#### LOCATION

- Internal and external
- Under damp proof membranes

#### SUBSTRATES

- New and existing concrete, damp or moisture vulnerable concrete, ceramic and quarry tiled floors, steel decks, timber floors (contact ARDEX Technical Services)

#### FLOOR COVERINGS

- Linoleum, vinyl, carpet
- Ceramic and quarry tiles
- Floating timber

#### COVERAGE

- 12m<sup>2</sup> at 1mm, 4m<sup>2</sup> at 3mm

#### THICKNESS

- Feather edge to 12mm
- Bulkfill 12-30mm with 2-5mm aggregate

#### DRYING TIME

- Walkable from 2 hours
- Ready for most floor coverings from 24 hours



#### ARDEX ARDITEX NA QUICK FACTS

- Low odour – User friendly
- Superior flow – Self smoothing
- Rapid hardening – Install many floor coverings from 4 hours
- Versatile – Timber and damp concrete substrates



CONTACT US  
1300 788 780 | [www.ardexaustralia.com](http://www.ardexaustralia.com)



Download the Ardex app  
(search for 'ARDEX Australia')



SYSTEMARDEX  
PREMIUM PERFORMANCE