FLOORING

ARDEX LQ92

Undertile Levelling Compound

ARDEX LQ 92 is a cement-based underlay for levelling uneven concrete floors prior to tiling. Not recommended for use under vinyl coverings. It is self smoothing and you can tile over it after approximately 4 hours. It is suitable for use with underfloor heating and may be mixed with ARDEX Abalastic liquid when incorporating heating wires. **LOW VOC**

LOCATION

- Internal, External
- External (not subject to freeze/thaw)

SUBSTRATES

Concrete

SURFACES

Floors

COVERAGE

20kg unit covers approximately 3.8m² at 3mm

BED THICKNESS

- 10mm down to feather edge
- For thicknesses over 10mm and up to 25mm, mix with 2mm 5mm aggregate
- For ramping mix with up to 10kg of coarse dried sand to achieve a trowelable non-flowing screed

COLOURS

Grey

PACKAGING

20kg



ARDEX LQ 92 QUICK FACTS

- Self smoothing provides level concrete floors, perfect for tiling
- Polymer modified can be applied from feather edge up to 25mm
- Early walkability can be walked on or tiled over after 4 hours
- Cement based compatible with ARDEX cement based tile adhesives









Download on the App Store

Download the Ardex app (search for 'ARDEX Australia')

CODE

10146

