


WATERPROOFING

ARDEX WPM 130 *Builder's Express*

Construction and Bathroom Membrane

Acrylic PU water-based waterproofing membrane developed for high performance undertile waterproofing. **LOW VOC** 

- Tough flexible film
- Meets Green Building Council of Australia Greenstar requirements IEQ-13, IEQ-11
- Can be tiled over – good adhesion with ARDEX tile adhesives
- Suitable for use under resilient flooring
- Excellent adhesion to a wide range of substrates
- Fast drying, 4 hours on decks and some applications
- Class III Membrane, as per AS/NZS 4858 Wet Area Membranes

TYPICAL APPLICATIONS

- Internal and external

SUBSTRATES

- Concrete
- Renders and screeds
- Engineered screeds
- Fibre cement sheets
- Plywood

COVERAGE

This will vary with the porosity of the substrates. Two coats are recommended for optimum performance. A 20kg unit (15 Litres) will cover approximately 9m² on floors and walls.

COLOURS

- Light blue

DRYING TIME

- Recoat time: 2–4 hours between first and second coats
- Ready to tile: 4 hours
- Ready for resilient flooring: After 24 hours

VOC CONTENT

- 42g/L

PACKAGING

15L (20kg) pails

CODE

38791



ARDEX WPM 130 *Builder's Express*

QUICK FACTS

- Tile in 4 hours
- Modified polyurethane acrylic waterproof membrane
- Excellent adhesion with ARDEX tile adhesives
- Suitable for under resilient flooring



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE