## TILING

# ARDEX X17

### Flexible Non Slump Wall and Floor Tile Adhesive

ARDEX X 17 is a white polymer fortified cement-based wall and floor tile adhesive that has been specially formulated with mastic type properties. ARDEX X 17 has an extended open time, is non slump and flexible. Mix with water to achieve a mortar suitable for internal and external use in residential and light commercial applications. ARDEX X 17 meets the Green Building Council of Australia Green Star IEQ-13 requirements for Ceramic Tile Adhesives. Low voc

#### **TILE TYPES**

Fully vitrified and ceramic tiles, porcelain, natural stones (excluding moisture) sensitive) and mosaics.

#### **SUBSTRATES**

- Concrete, renders, screeds
- Fibre-cement sheet, plasterboard on walls
- Compressed fibre-cement sheet on floors
- ARDEX liquid applied undertile waterproofing membranes
- Existing ceramic tiles (internal dry areas)
- Ceramic Tile Underlay (CTU)

#### LOCATION

Internal, External (Not suitable for swimming pools)

#### **SURFACES**

Floors, Walls

#### **COLOURS**

White

#### **COVERAGE**

- Walls: 10m<sup>2</sup> per 20kg
- Floors: 6m<sup>2</sup> per 20kg

#### PACKAGING

20kg

#### CODE

25276





**CONTACT US** 



Download the Ardex app (search for 'ARDEX Australia')



#### ARDEX X17 **QUICK FACTS**

- Superior flexibility achieves S1 classification
- Extended open time
- Non slump ideal for large format and heavy tiles
- Great workability with low sand content





SYSTEMARC PREMIUM PERFOR