

ARDEX X56

Highly Flexible Tile Adhesive

A highly flexible tile adhesive that is also fast setting. This makes ARDEX X 56 suitable for tiling directly to timber and over heated slabs. **LOW VOC**



TILE TYPES

- Ceramic, fully vitrified, porcelain, mosaics, natural stone (excluding moisture sensitive)

SUBSTRATES

- Cement renders/screeds, concrete, aerated concrete
- Internal timber (particleboard, plywood, mdf, cork) (priming required with ARDEX Optima or ARDEX P 82) with the exception of unbonded timber
- Fibre-cement sheet, plasterboard
- ARDEX undertile liquid applied waterproofing membranes
- Compressed fibre-cement sheet
- Existing ceramic tiles (where glaze is removed)

LOCATION

- Internal, External (with adequate falls to waste)
(Not suitable for swimming pools to commercial floors subject to heavy traffic)

SURFACES

- Floors, Walls

COLOURS

- Light Grey

COVERAGE

- Walls: 8m² per 15kg
- Floors: 6m² per 15kg

PACKAGING

- 15kg

CODE

10227



ARDEX X56 QUICK FACTS

- Fast setting - grout after 4 hours
- Suitable for early age concrete
- Highly flexible



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE