

ARDEX AF 171

Indoor Water Based Adhesive

ARDEX AF 171 is a water based adhesive for internal use.

LOW VOC 

LOCATION

- Internal

SUBSTRATES

- Hardboard underlayment board approved to AS 2458
- Cementitious underlayment
- Dry concrete where there is less than 80% RH when tested with in situ probe test

Contact ARDEX Technical Services for other substrates including terrazzo, ceramic tiles and metal substrates.

FLOOR COVERINGS

- Vinyl plank
- Wall sheet vinyl
- Sheet vinyl
- Linoleum
- Direct stick and double bond carpet installation
- Acoustic mat

COVERAGE

- Using a 1.6x1.6x1.6mm V-Notch trowel approximately 5.0m²/L
- Using a 0.8x1.6x0.8mm U-Notch trowel approximately 7.0m²/L

WORKING TIME

- Approximately 15 - 20 minutes

SET UP TIME

- Approximately 10 - 15 minutes

PACKAGING

- 15L pail containing 18kg of adhesive

CODE

38564



ARDEX AF 171 QUICK FACTS

- Fast grab with very strong ultimate bond
- Excellent dimensional stability
- Excellent resistance to plasticiser migration



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE