ARDEX WPM002 MEMBRANE-ARDEX FEATHER FINISH SMOOTHING-CEMENT VINYL WALL FINISH VINYL FLOORING MINIMUM FALL 1:100 VINYL COVE FILLET -UNBONDED ARDEX A38, 45mm MIN COMPRESSIBLE FOAM THICKNESS AT PERIMETER OF SET DOWN 4 2 LAYER PLASTIC SLIP SHEET OVER WPM002 4 MEMBRANE

(ARDEX)

NOTES

The technical details, recommendations & other information contained in this drawing is given in good faith & represents the best of our knowledge and experience at the time of design. It is your responsibility to ensure that our products are used used correctly in accordance with any applicable Australian Standard, our instructions & recommendations are only for the uses they are intended. We also reserve the right to update information without prior notice to reflect our ongoing research and development program.

1/ All Ardex Products to be installed in accordance with datasheet.
2/ All systems to comply with relevant Australian Standards

Country specific recommendations, depending on local standards, codes of practice, building regulations and industry guidelines may effect specific installation recommendations.

The supply of our products and services are also subject to certain terms, warranties & exclusions which are available to you on request.

FILE NAME	ADDEV ALICTDALIA
VinylOverMembraneUnbondedScreed	ARDEX AUSTRALIA
DRAWN	www.ardexaustralia.com
1/12/2015 by MZ	www.ardcxadstrana.com
CHECKED	SCALE NTS
	IIIO
SIZE A4	DRAWING
A4	CODE VOMUS