



ARDEX CE 903

Ultra Flow Injection Grout

Highly fluid

Extremely durable

No admixtures required

No segregation with zero bleed

ARDEX Australia Pty Ltd

2 Buda Way,
Kemps Creek, NSW 2178
Phone: 1300 788 780
Email: technicalservices@ardexaustralia.com
www.ardexaustralia.com

ARDEX New Zealand Ltd

15 Alfred Street, Onehunga Auckland,
New Zealand 1061
Phone: 0800 227 339
Email: info@ardexnz.com
www.ardex.co.nz

ARDEX CE 903

Ultra Flow Injection Grout

DESCRIPTION

ARDEX CE 903 is a ultra highly fluid, low bleed or segregation cement injection grout suitable for a wide range of civil engineering applications.

ARDEX CE 903 is designed for demanding injection applications with superior penetration into tight joints, fissures, and pores, providing a watertight grouted rock or soil mass. The physical properties of the composite are a function on the soil type, saturation, compaction, and moisture content.

RECOMMENDED USES

- Soil Injection
- Curtain Grouting
- Contact grouting
- Ground stabilisation
- Rock Fissure grouting
- Tunnels pre and post excavation grouting

ADVANTAGES

- Highly fluid
- Long pump life
- Long term durability
- No admixtures required
- No segregation with zero bleed

PREPARATION

ARDEX CE 903 is typically pumped as a single component, the gel time may be adjusted by the addition of an approved accelerator into the base mix prior to mixing and pumping. Trials are recommended before application if using an accelerator to confirm dose rates. Consult ARDEX for additional information.

MIXING

Measure approximately 80% of the required water into a clean suitable sized pail and then add the entire contents of the bag while mixing with a heavy-duty electric drill on medium speed (approximately 680rpm). Add the remaining water and mix for about 2 – 3 minutes or until it is fully homogenized. The mixed material must be poured immediately for best results.

PUMPING

Once the grout has been mixed you need an effective pumping method to deliver it to the area of application. Various models of mixers are available for use, all with varying specifications. It is important to match your application's specifics with the capabilities of the mixer and pump. ARDEX can recommend the right mixer for your project.

Prior to pumping grout, rinse the mixer and charge the pump hopper with sufficient water to flush and cool the pump and all grout lines thoroughly. Check to ensure that all lines and hoses are clear and unobstructed. Once grout is mixed, it is important to keep it agitated continuously prior to pumping. It is important to pump continuously.

Following completion, dispose of excess production material in consideration of the environment. Carefully wash out mixer tanks and agitators into the pump hopper and pump the resulting washout material through the grout hoses to a suitable disposal site.

APPLICATION TEMPERATURES

The mix water's temperature should be kept as low as possible to prevent the grout from hydrating too rapidly. As with the water temperature, the higher the air temperature the more quickly the grout hydrates and sets. ARDEX specify mixing times and set times at an ambient temperature of 20°C. These times vary with temperature fluctuations, and adjustments will be required to compensate for this. In some cases, it may be necessary to cool the material, the mix water, keep the temperature as low as possible. It is estimated that every 10°C increase in temperature will halve the product set time. Likewise, every 10°C reduction will double the set time. ARDEX should be consulted for extreme temperature applications.

PACKAGING

20kg bag

CLEAN UP

All grouting equipment shall be thoroughly washed with clean water after grouting operations for that day are completed.

SHELF LIFE

ARDEX CE 903 has a shelf life of 12 months when stored in the original unopened packaging in a dry place at 23°C and 50% relative humidity.

ARDEX CE 903

Ultra Flow Injection Grout

TECHNICAL DATA

Mixing Ratio	12 ltrs - 40 ltrs of clean water per 20kg bag 0.6 - 2:1 (w/r)
Coverage	18 ltrs - 40 ltrs per 20kg bag

CHARACTERISTIC	TEST METHOD	TEST RESULT
Flow consistency	Marsh funnel flow	< 40 Secs
Bleed		< 0.5%
Setting time: Initial Final	ASTM C953	8 - 10 hrs < 24 hrs

ARDEX CE 903

Ultra Flow Injection Grout

SAFETY DATA

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure. Do not breathe dust/fume. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. Immediately call a POISON CENTER/doctor/physician/first aider. IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Before any substrate preparation, installation or finishing methods relating to ARDEX product are undertaken, please be aware of any potential risks and use appropriate PPE (personal protective equipment). This may involve contacting substrate manufacturers for Safety Data Sheets.

GUARANTEE

ARDEX Australia Pty Ltd ("we" or "us") guarantees this product ("our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of purchase. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or compensation, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow published instructions or any act or circumstance beyond our control, including shade variations and efflorescence. If you wish to make a claim under this guarantee you must notify us (ARDEX Australia Pty Ltd, 2 Buda Way, Kemps Creek, NSW 2178; Toll Free: 1800 224 070; Email: technicalservices@ardexaustralia.com) and provide evidence of your purchase of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2025.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.

This data sheet was issued in December 2025 and is valid for 3 years, in some instances a newer version may be published. Always refer to www.ardexaustralia.com for the latest technical data from ARDEX Australia Pty Ltd.