



---

# ARDEX

# Pressure Seal

---

---

ARDEX Australia Pty Ltd  
20 Powers Road  
Seven Hills NSW 2147  
Tel: (02) 9851 9199  
Fax: (02) 9674 5621  
Email: [techinfo@ardexaustralia.com](mailto:techinfo@ardexaustralia.com)  
Internet: [www.ardex.com](http://www.ardex.com)

ARDEX New Zealand Ltd  
32 Lane St, Woolston  
Christchurch, New Zealand  
Tel: (03) 384 3029  
Fax: (03) 384 9779  
Email: [techinfo@ardexaustralia.com](mailto:techinfo@ardexaustralia.com)  
Internet: [www.ardex.com](http://www.ardex.com)

# ARDEX Pressure Seal

---

## DESCRIPTION

ARDEX Pressure Seal is designed for termination of ARDEX TPO membrane against smooth walls in all roofing systems.

## PREPARATION

Substrate must be sound, smooth, dry and free from dust, dirt, oil and other contaminants prior to installation. Wall areas above Pressure Seal must be waterproof.

When site cutting is necessary, remove any burrs from the bar and clean up shavings, etc. that may occur from cutting.

## APPLICATION

Install a general purpose sealant behind top of flashing. Anchor the Pressure Seal through the pre-punched holes with an acceptable fastener at a rate to maintain a good, tight compression to the wall against the general purpose sealant. Remove excess flashing material above the bar and install General Purpose Sealant into the channel. Consult ARDEX specifications and details for specifics.

## COVERAGE

In accordance with the length of the detail.

## CHARACTERISTICS

### Technical

<b>Material</b>	corrosion-resistant aluminum
<b>Length (m)</b>	3.10
<b>Width (mm)</b>	35
<b>Thickness (mm)</b>	2.2

### PACKAGING/STORAGE/SHELF LIFE

Packaging:	25 in a pack. (77.5m).
Storage:	Store in original unopened container protected from the weather.
Shelf life:	Unlimited.

## DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

### ARDEX Australia Pty Ltd

New South Wales	Ph (02) 9851 9100	Fax (02) 9838 7970
Queensland	Ph (07) 3817 6000	Fax (07) 3881 3188
Victoria/Tasmania	Ph (03) 9308 9255	Fax (03) 9308 9332
South Australia	Ph (08) 8268 2511	Fax (08) 8345 3207
Western Australia	Ph (08) 9256 8600	Fax (08) 9455 1227

### ARDEX New Zealand Ltd

Auckland	Ph (09) 5800 005	Fax (09) 5799 963
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 3843 029	Fax (03) 3849 779

**Technical Services Toll Free: 1800 224 070**