



# 1. SUBSTRATE PREPARATION

Begin by mechanically preparing the substrate to remove contamination, curing compounds, additives and opening the pores of the substrate. This assists in proper priming of the substrate. Rectify cracking and repair surfaces with the following:



## **ARDEX RA 56**

Low-Viscosity Rigid Hybrid Polyurethane Crack & Spall Repair

#### **ARDEX RA 88 PLUS**

Multi-Purpose Non Sag Epoxy Repair Adhesive

#### **CONCRETE CRACK LOCK**

Carbon Fibre Crack Bridging Stitch which can used with ARDEX RA 88 PLUS

#### **ARDEX A45**

Rapid Hardening & Drying Repair Mortar for internal repairs and dormant cracks

If floor moisture is present, install a green slab sealer or moisture barrier. Note sand seeding or repriming may be necessary:



#### **ARDEX PU 30 RAPID**

Polyurethane Primer & Green Slab Sealer up to 98% RH. Will not prevent rising damp.

#### **ARDEX WPM300**

A two component water based epoxy polyamide membrane/barrier coating to prevent rising damp.

#### **ARDEX WPM368**

Single part barrier membrane which prevents rising damp.

# 2. INSTALL SMOOTHING/SELF LEVELLING



#### **ARDEX FINE FINISH**

Smoothing for thicknesses featheredge - 3mm

#### **ARDEX FEATHER FINISH**

Rapid drying smoothing for thicknesses featheredge - 3mm

## ARDEX K 120

Economic levelling for thicknesses 2.5 - 12mm

#### ARDEX K220

Low odour levelling for thicknesses 2 - 20mm

## **ARDEX K12 NEW**

Super smooth levelling for thicknesses 1.5 - 35mm

# **ARDEX K10 REACTIV8**

Long open time levelling for thicknesses 1.5 - 15mm

### ARDEX K15

Fibre reinforced levelling for thicknesses featheredge - any depth

#### **ARDEX K55**

Rapid drying levelling for thicknesses 1 mm - any depth

## **ARDEX ARDITEX NA**

Flexible levelling for thicknesses featheredge - 12mm

# 3. ADHESIVE FIX VINYL



## **ARDEX AF 142**

Fast grab vinyl adhesive

# ARDEX AF 180 MS

Heavy duty adhesive for areas with direct sunlight and moisture

Refer to the most current product datasheet and/or technical bulletin at www.ardexaustralia.com for installation instruction