



TECHNICAL BULLETIN – TB208

MAINTENANCE PROCEDURE FOR LIQUID APPLIED MEMBRANES

31st July 2024

INTRODUCTION & SCOPE

This document recommends items and time intervals required for the ongoing maintenance and performance of a roof or other area coated with a liquid-applied membrane as the final finished surface. Adherence to these procedures will ensure the continued coverage of the warranty during the nominated period.

WHY INSPECT?

- ① The roof is exposed to all elements, including foot traffic, which slowly ages the membrane until its service life ends.
- ① A roof requires regular inspections and prompt repairs.
- ① Studies have shown that a roof not regularly maintained will only last half its expected life.
- ① Don't assume that a warranty will help.
- ① If you cannot show that the roof has been maintained, you may not have a case to enforce a claim on the manufacturer's warranty.
- ① Experienced facility managers know that a roof should be inspected at least twice a year to maintain this warranty.
- ① Always engage an experienced and competent engineer/contractor who specializes in external roofing and membranes.

PERIODIC ROOF INSPECTIONS.

- 1) Inspections are mandatory every 6 months and immediately after any work is completed on the roof.
- 2) A "Roof Maintenance Inspection Checklist" should be used in conjunction and to assist in the inspection procedure.
- 3) An inspection checklist form is located at the back of this guide. This will help to ensure a complete and thorough inspection.
- 4) Notes and photos should be taken, and a sketch should be completed illustrating areas of concern.
- 5) Reports of previous inspections should be reviewed before subsequent roof inspections are done.

AREAS TO INSPECT

The following are critical areas for any inspection.

Gutters and drains for twigs, leaves, dirt, and debris. These can cause damage due to the restriction of normal flow, preventing positive drainage.

Check the screens, strainers, fasteners, and seals to ensure that there is no damage to these items or leakage.

Flashings, parapet walls, expansion/control joints for cracks or splits, and ensure



that they are sealed effectively.

Masonry walls should be checked for moisture penetration, deterioration or de-lamination of the coating.

Surface area of the roof for blisters, physical and mechanical damage caused by equipment, hail, vandalism, and or excessive foot traffic. This also includes any unauthorized work/maintenance associated with HVAC, electrical, plumbing, or equipment installations. Check the coating in these areas to ensure there is no damage to the coating.

WHEN TO CALL THE CONTRACTOR.

Before any work/alterations/rectifications commence, call the contractor.

If blisters, leaks, or damage are noted, the installation contractor must be contacted immediately. Failure to do this will void your warranty if it is still within this period.

Also, contact the company that issued the warranty in writing with details. At some point, the system may require rejuvenation or renewal. In this case, contact the original contractor for an inspection/report.

If the contractor does not adequately address any questions concerning the system, contact the manufacturer.

PREVENTATIVE MAINTENANCE.

Roofs should not be used to store building materials, signs, or other unnecessary equipment. This will require a complete re-assessment of the roof.

Limit foot traffic as much as possible, and maintenance personnel should be the only foot traffic on the roof.

If regular foot traffic is anticipated, walkways should be installed to protect the roof membrane.

Prevent damage to the roof membrane from exposure to chemicals, solvents, petroleum-based products, and gases from exhaust systems, as these will promote rapid deterioration and decomposition of the coating system.

All service lines (PVC, metal) must not lie directly on the coating.

ANY SUBSEQUENT DAMAGE/DEFECTS IN THE MEMBRANE SYSTEM.

The original contractor must be informed to arrange an inspection and to carry out rectification work to retain the remaining warranty period on the system.

If you notice internal leaks, contact the original contractor so he may inspect the roof to confirm if the leaks are attributable to damage.

A sample inspection plan is shown on the following page.



Semi-annual maintenance inspection checklist

Roofing system substrate: _____	Applicator: _____
Building: _____	Roof selection: _____
Inspected by: _____	Completion date: _____
Warranty team: _____	Inspection date: _____

	PROBLEM		OBSERVATIONS	REPAIRS		
	NO	YES		Repairs by whom		Date
				Owner	Applicator	
ROOF CONDITION						
General						
Debris						
Walkways						
Substrate						
Leaks						
Drainage						
Roof drains						
Scuppers						
Gutters						
Downspouts						
Ponding						
Membrane						
Bare spots						
Adhesion						
Cracks						
Pinholes						
Mechanical damage						
Blisters						
Cracks						
Vandalism						
Bird damage						
Storm damage						
Soft & spongy						
Wet						
PENETRATION						
Pipes						
A/C Units						
Vents						
Skylights						
Expansion joints						
Ducts						
Walls						

Use the following symbols when preparing a roof sketch:

P>	Photographs	EX	Excessive Ponding	UC	Uncurred coatings	E	Exposed foam
O	Roof drains	P	Pinholes	DT	Flashing or Edge treatment defect	OS	Overspray
X	Mechanical drainage	S#	Slit number			OF	Off ration SPF
FB	SPF blister	TC	Thin coating	FC	SPF cracks		
CB	Coating blister	FT	Rough foam texture	CC	Coating cracks		



Building tomorrow

IMPORTANT

This Technical Bulletin provides guideline information only and is not intended to be interpreted as a general specification for the application/installation of the products described. Since each project potentially differs in exposure/condition specific recommendations may vary from the information contained herein. For recommendations for specific applications/installations contact your nearest Ardex Australia Office.

DISCLAIMER

The information presented in this Technical Bulletin is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of a product for a particular application. Users are asked to check that the literature in their possession is the latest issue.

Australia: 1300 788 780

New Zealand: 643 384 3029

Web: www.ardexaustralia.com

email: technical.services@ardexaustralia.com

Address: 2 Buda Way, Kempers Creek NSW 2178